# veranda oak



Comfort Enhanced NE+ | CC1216

#### Reducer

WP1272\_00016RD



0.708 in.

Used to transition between two flooring heights, providing a smooth change.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.51

TRIM WIDTH (in.)

1.77



#### T-Mold

WP1272\_00016TM



Covers the seam between two floors of equal height.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.51

TRIM WIDTH (in.)

1.71



#### Quarter Round

WP1272\_00016QR

Installed along the base of the wall to cover gaps and add a decorative touch.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.708

TRIM WIDTH (in.)

0.708



2.07 in.

#### Threshold

WP1272\_00016BT



2.01 in.

Creates a smooth transition between rooms or doorways, often at entryways.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.51

TRIM WIDTH (in.)

1.73



## Flush Stair Nose

WP1272\_00016FS

Provides a clean, flush edge where the stair nose meets the floor.  $\,$ 

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.75

TRIM WIDTH (in.)

2.07



### Overlap Stair Nose

WP1272\_00016OS

Covers the edge of the stair, overlapping the flooring of the step.



94.5

TRIM HEIGHT (in.)

1.5

TRIM WIDTH (in.)

2.01



## veranda oak




4.49 in.

Comfort Enhanced NE+ | CC1216

12.2









Stair Treads Tip: Complete the look on the top stair with a flush or overlap stair nose.

4.49