fireside oak

Comfort Enhanced | CC1202

Reducer

WP1272_00002RD



0.708 in.

Used to transition between two flooring heights, providing a smooth change.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.51

TRIM WIDTH (in.)

1.77



T-Mold

WP1272_00002TM



Covers the seam between two floors of equal height.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.51

TRIM WIDTH (in.)

1.71



Quarter Round

WP1272_00002QR

Installed along the base of the wall to cover gaps and add a decorative touch.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.708

TRIM WIDTH (in.)

0.708



2.07 in.

Threshold

WP1272_00002BT



2.01 in.

Creates a smooth transition between rooms or doorways, often at entryways.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.51


TRIM WIDTH (in.)

1.73



Flush Stair Nose

WP1272_00002FS



TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.75

TRIM WIDTH (in.)

2.07



Overlap Stair Nose

WP1272_00002OS

Covers the edge of the stair, overlapping the flooring of the step.



94.5

TRIM HEIGHT (in.)

1.5

TRIM WIDTH (in.)

2.01



fireside oak



4.49 in.

Comfort Enhanced | CC1202



INCLUDED WITH STAIR TREADS

7.48

12.2 in.

The vertical piece between the stair steps.

TRIM LENGTH (in.) 44.09

TRIM THICKNESS (in.)

TRIM WIDTH (in.)


7.48

.15



Stair Tread

WP1272_00002ST



The horizontal surface of the stair, covering the entire stepping area.

TRIM LENGTH (in.)

50

TRIM HEIGHT (in.)

1.73

TRIM WIDTH (in.)

12.2



Square Stair Tread

WP1272_00002SQST

The horizontal surface of the stair, covering the entire stepping area with a square-edged nose.

TRIM LENGTH (in.)

50

TRIM HEIGHT (in.)

1.73

TRIM WIDTH (in.)

12.2



Flush Square Stair Nose

WP1272_00002FSQ

Provides a clean, flush edge where the square-edged stair nose meets the floor

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

1.73

TRIM WIDTH (in.)

4.49



Stair Treads Tip: Complete the look on the top stair with a flush or overlap stair nose.