toasted oak

Comfort NE | CC0817

Reducer

WP0860_00017RD



0.708 in.

Used to transition between two flooring heights, providing a smooth change.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.39

TRIM WIDTH (in.)

1.77



T-Mold

WP0860_00017TM



Covers the seam between two floors of equal height.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.39

TRIM WIDTH (in.)

1.71



Quarter Round

WP0860_00017QR

Installed along the base of the wall to cover gaps and add a decorative touch.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.708

TRIM WIDTH (in.)

0.708



2.07 in.

Threshold

WP0860_00017BT



2.01 in.

Creates a smooth transition between rooms or doorways, often at entryways.

TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.35


TRIM WIDTH (in.)

1.73



Flush Stair Nose

WP0860_00017FS



TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

0.75


TRIM WIDTH (in.)

2.07



Overlap Stair Nose

WP0860_00017OS



TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

1.5

TRIM WIDTH (in.)

2.01



toasted oak



Comfort NE | CC0817

Riser

INCLUDED WITH STAIR TREADS

12.2 in.

The vertical piece between the stair steps.

TRIM LENGTH (in.)

44.09

TRIM THICKNESS (in.)

TRIM WIDTH (in.)

7.48

.15



Stair Tread

WP0860_00017ST



TRIM LENGTH (in.)

50

TRIM HEIGHT (in.)

1.73

TRIM WIDTH (in.)

12.2



Square Stair Tread

WP0860_00017SQST

The horizontal surface of the stair, covering the entire stepping area with a square-edged nose.

Flush Square Stair Nose

WP0860_00017FSQ

Provides a clean, flush edge where the square-edged stair nose meets the floor

4.49 in.

TRIM LENGTH (in.)

50

TRIM HEIGHT (in.)

1.5

TRIM WIDTH (in.)

12.2



TRIM LENGTH (in.)

94.5

TRIM HEIGHT (in.)

1.73

TRIM WIDTH (in.)

4.49



Stair Treads Tip: Complete the look on the top stair with a flush or overlap stair nose.